




FICHA TÉCNICA

Eléctrico												
1	Cortocircuito (2" Electrodo)	KV	ASTM-D-149	3.5	4.0	5.5	7.0	9.5	12.5	13.5	15.5	
2	Resistencia Superficial	Ohm	ASTM-D-257	10 ¹²	10 ¹²	10 ¹²	10 ¹²	10 ¹²	10 ¹²	10 ¹²	10 ¹²	
3	Volumen Resistencia @ RT	Ohm cm	ASTM-D-257	10 ¹⁶	10 ¹⁶	10 ¹⁶	10 ¹⁶	10 ¹⁶	10 ¹⁶	10 ¹⁶	10 ¹⁶	
4	Permitividad	---	IEC 250									
	23°C,50Hz											3.26
	23°C,1kHz											3.24
	23°C,10 kHz											3.21
	0°C,50Hz											3.26
	50°C,50Hz											3.27
	100°C,50Hz											3.35
150°C,50Hz	3.65											
5	Factor de Disipación	---	IEC 250									
	23°C,50Hz											0.002
	23°C,1kHz											0.0055
	23°C,10 kHz											0.011
	0°C,50Hz											0.004
	50°C,50Hz											0.0015
	100°C,50Hz											0.007
150°C,50Hz	0.006											
6	Coefficiente de Expansión térmica entre 20°C & 50°C	1/ K(cm/cm °C) 1/ K(cm/cm °C)	-- --	34X10 ⁻⁶ (MD) 28X10 ⁻⁶ (TD)								