



FICHA TÉCNICA

Dimensiones y valores

Sección nominal mm ²	Equivalencia aproximada en AWG	Composición nominal nº hilos x Ø mm	Resistencia lineal máxima a 20°C Ω/km	Diámetro exterior nominal mm	Masa lineal aproximada kg/km
0.5	20	16 x 0.20	52.4	2.0	8.00
1	18	32 x 0.20	19.5	2.3	13.4
1.5	16	30 x 0.25	13.3	2.7	19.8
2.5	14	50 x 0.25	7.98	3.4	30.7
4	12	56 x 0.30	4.95	4.2	48
6	10	84 x 0.30	3.39	5.2	73
10	8	80 x 0.40	1.95	7.0	129
16	6	126 x 0.40	1.24	8.6	198
25	4	196 x 0.40	0.795	10.4	295
35	2	276 x 0.40	0.565	11.9	399
50	1/0	396 x 0.40	0.393	14.1	562
70	2/0	360 x 0.50	0.277	15.9	759
95	3/0	485 x 0.50	0.210	18.2	1024
120	4/0	608 x 0.50	0.164	20.3	1275
150	300 MCM	756 x 0.50	0.132	22.8	1587
185	350 MCM	944 x 0.50	0.108	24.8	1952
240	500 MCM	1221 x 0.50	0.0817	28.8	2560
300	600 MCM	1525 x 0.50	0.0654	31.5	3095
400	750 MCM	2037 x 0.50	0.0495	35.4	5130